



# Indoor Full Color LED Video Wall

## TV-PG093-GM



### Description:

It has the characteristics of seamless splicing, perfect display, long service lifespan, fast frame changing speed, high refresh rate, good uniformity, wide viewing angle, high grayscale, natural color reproduction, etc. It is widely used in command and dispatch, security monitoring, video conference, studio display, and various conference display occasions.

### Feature:

- \* Used to monitor and display the situation in real time and play various advertisements.
- \* Seamless splicing, and no visual black seam on the screen.
- \* The display unit is flexible and compact, and supports flat and curved splicing.
- \* DC low-voltage power supply, natural heat dissipation, no fan, and zero noise.
- \* When a failure occurs, it only needs to maintain a single LED pixel or a single module, realizing low maintenance cost and fast maintenance speed.
- \* Support picture correction, adopt gamma correction technology, achieve point-by-point brightness and color correction.
- \* Support smart light control, smartly adjust brightness, improve picture comfort, and save energy.
- \* With ultra-wide viewing angle, the screen has a larger viewing range, and the picture is still clear when viewed from any angle.
- \* Support ultra-high refresh speed, good screen continuity and high screen fluency.
- \* The picture is delicate and realistic, and the grayscale is still excellent in low brightness.
- \* Support UHD display, adopt unique image quality enhancement technology to effectively improve image clarity, and the high-speed picture is smooth and no smear.
- \* Support integrating 3D, touch screen and somatosensory games and other functions to improve entertainment and interactivity.
- \* Wireless connection, clean and safe back design.
- \* Support hard connection, full hot swap.

### Specifications:

|                                                                                                                                                       |                                                                                                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Model                                                                                                                                                 | A0.9375                                                                                                              |
| LED encapsulation                                                                                                                                     | 4 in 1 integrated packaging & common cathode (cc)                                                                    |
| Pixel pitch                                                                                                                                           | 0.9375mm                                                                                                             |
| Resolution                                                                                                                                            | 113777 pixels/m <sup>2</sup>                                                                                         |
| Lamp bead/IC                                                                                                                                          | Naionstar gold wire/high refresh rate                                                                                |
| Pixel configuration                                                                                                                                   | 1R1G1B                                                                                                               |
| Module resolution                                                                                                                                     | 320*180                                                                                                              |
| Module size (mm)                                                                                                                                      | 300*168.75                                                                                                           |
| Cabinet resolution                                                                                                                                    | 642*360                                                                                                              |
| Cabinet size (mm)                                                                                                                                     | 600*337.5                                                                                                            |
| Cabinet weight                                                                                                                                        | 7.8Kg/pc                                                                                                             |
| Working voltage                                                                                                                                       | DC+4.2V                                                                                                              |
| Best viewing distance                                                                                                                                 | ≥3m                                                                                                                  |
| Horizontal viewing angle                                                                                                                              | ≥175°                                                                                                                |
| Vertical viewing angle                                                                                                                                | ≥175°                                                                                                                |
| Maintenance method                                                                                                                                    | Front maintenance                                                                                                    |
| Graphics card                                                                                                                                         | DVI/HDMI/DP                                                                                                          |
| Video signal                                                                                                                                          | Compatible with PAL/NTSC/SECAM format, support S-Video; VGA; RGB; CompositeVideo; SDI; DVI; RF; RGBHV; YUV; YC, etc. |
| Control mode                                                                                                                                          | Synchronous control                                                                                                  |
| Drive device                                                                                                                                          | Constant current drive                                                                                               |
| Refresh rate                                                                                                                                          | ≥3840Hz                                                                                                              |
| Frame rate                                                                                                                                            | ≥60Hz                                                                                                                |
| Scanning method                                                                                                                                       | 46s                                                                                                                  |
| Brightness                                                                                                                                            | 200~800CD/m <sup>2</sup>                                                                                             |
| Grayscale                                                                                                                                             | 12/14/16bit                                                                                                          |
| Contrast                                                                                                                                              | ≥10000:1                                                                                                             |
| Decay rate (after 3-year work)                                                                                                                        | ≤15%                                                                                                                 |
| Brightness adjustment method                                                                                                                          | Auto/Manual 1~100%                                                                                                   |
| Computer operating system                                                                                                                             | WIN98/2000/WIN*P/WINVista/WIN7                                                                                       |
| MTBF                                                                                                                                                  | ≥20000H                                                                                                              |
| Lifespan                                                                                                                                              | ≥100000H                                                                                                             |
| Failed rate                                                                                                                                           | ≤1/100000 and no continuous failed pixels                                                                            |
| Software                                                                                                                                              | Professional LED video wall system programming software                                                              |
| Storage temperature                                                                                                                                   | -35°C~+85°C                                                                                                          |
| Working temperature                                                                                                                                   | -20°C~+60°C                                                                                                          |
| Working voltage (AC)                                                                                                                                  | 220V±10%/50Hz or 110V±10%/60Hz                                                                                       |
| Average power consumption                                                                                                                             | ≤179W/m <sup>2</sup>                                                                                                 |
| Maximum power consumption                                                                                                                             | ≤538W/m <sup>2</sup>                                                                                                 |
| Cabinet material                                                                                                                                      | Die-cast aluminum cabinet                                                                                            |
| Brightness uniformity                                                                                                                                 | ≥99%                                                                                                                 |
| Protection class                                                                                                                                      | IP5X                                                                                                                 |
| With an LCD panel, it supports the installation accuracy display, single cabinet detection, working temperature/humidity display and other functions; |                                                                                                                      |
| Automatic detection of vertical and horizontal angles;                                                                                                |                                                                                                                      |
| Automatic detection of the internal temperature of the cabinet; when it is overheated, the LED light bar next to the LCD panel will turn blue.        |                                                                                                                      |